


HW-TSB001



Type 項次	Material 材質	Delivery 交貨日
HW-TSB001	Brass 黃銅	10 Working Days 10 個工作日

Choose The Type Of Flanged 選擇法蘭樣式	I	II	III	IV

Type	d	Pitch	D	L1	D1	T	P.C.D.	K	W	W1	Allowable Dynamic Thrust(kN) 動態容許推力(kN)	Direction of thread 螺紋方向
HW-TSB001	(8)	1.5	15	20	30	5	22	4.3	-	-	1.47	Right 右 / Left 左
	10	2	20	24	36	5	26	4.3	22	-	2.55	
	12	2	22	30	44	5	31	5.4	24	-	3.92	
	*14	3	22	30	44	5	31	5.4	24	33	4.90	
	*16	3	28	35	51	6	38	6.6	30	38	6.67	
	18	4	32	40	56	6	42	6.6	34	-	8.72	
	*20	4	32	40	56	6	42	6.6	34	42	9.81	
	*22	5	36	50	61	7	47	6.6	40	47	12.36	
	*25	5	36	50	61	7	47	6.6	40	47	14.22	
	*28	5	44	56	76	8	58	9	48	58	17.95	
	*32	6	44	56	76	8	58	9	48	58	21.08	
	36	6	52	60	84	8	66	9	56	-	25.78	
40	6	58	70	98	10	76	11	62	-	33.83		
50	8	68	80	109	10	85	11	72	-	40.31		

※IV Type are available with * marked.


※d8 is applicable to Type I and II (Right-hand Thread)

※IV型僅限有*符號者

※d8僅限I型(右螺牙)、II型(右螺牙)

Order Ex. 訂購範例

HW-TSB001-d-□-□



螺紋尺寸
法蘭樣式(I/II/III/IV)
右/左螺紋