



HWLB-005



※ Including Seal 附油封

Type 項次	Material 材質	Hardness 硬度	Delivery 交貨日
HWLB-005	Outer Cylinder 外筒	Balls 滾珠	Retainer 保持器
	SUJ2	SUJ2	Stainless Steel(SUS) 不鏽鋼(SUS)
		58HRC~	10 Working Days 10 個工作日

Type	d	TOL.	D	TOL.	L	B	W	D1	Eccentricity (Max) 偏心(最大)	Rows of Balls 滾珠列數	Basic Ratingload C(動態)N (Dynsic)	Co(靜態)N (Static)
HWLB-005	3	0 -0.008	7	0 -0.009	10	-	-	-	0.008	4	69	105
	4	0 -0.008	8	0 -0.009	12	-	-	-	0.008	4	88	127
	5	0 -0.008	10	0 -0.009	15	10.2	1.1	9.6	0.008	4	167	206
	6	0 -0.009	12	0 -0.011	19	13.5	1.1	11.5	0.012	4	200	260
	8	0 -0.009	15	0 -0.01	24	17.5	1.1	14.3	0.008 0.012	4	274	392
	10	0 -0.009	19	0 -0.01	29	22	1.3	18	0.008 0.012	4	372	549
	12	0 -0.009	21	0 -0.013	30	23	1.3	20	0.008 0.012	4	510	784
	13	0 -0.009	23	0 -0.013	32	23	1.3	22	0.008 0.012	4	510	784
	16	0 -0.009	28	0 -0.013	37	26.5	1.6	27	0.008 0.012	4	774	1180
	20	0 -0.010	32	0 -0.016	42	30.5	1.6	30.5	0.010 0.015	5	880	1370
	25	0 -0.010	40	0 -0.016	59	41	1.85	38	0.010 0.015	6	980	1570
	30	0 -0.010	45	0 -0.016	64	44.5	1.85	43	0.010 0.015	6	1570	2740
	35	0 -0.012	52	0 -0.019	70	49.5	2.1	49	0.012 0.020	6	1670	3140
	40	0 -0.012	60	0 -0.019	80	60.5	2.1	57	0.012 0.020	6	2160	4020
	50	0 -0.012	80	0 -0.019	100	74	2.6	76.5	0.012 0.020	6	3820	7940
	60	0 -0.015	90	0 -0.022	110	85	3.15	86.5	0.017 0.025	6	4700	10000

Order Ex. 訂購範例

HWLB-005-d

Internal Diameter

內徑