



Type	W	L	Hole Type	ℓ1	ℓ2	ℓ3	d1	d2	t	VDI Code	
SZ-DMWP	125	50	A	75	25	-	13.5	20	13	VDI3357-A-181	
		80	C			-				75	VDI3357-A-182
		100				100				VDI3357-A-183	
		125				135				VDI3357-A-184	
		160				175				VDI3357-A-185	
		200				210				VDI3357-A-186	
	250	275		-							
	160	50	A	110	25	-	13.5	20	13	VDI3357-A-191	
		80	C			75				VDI3357-A-192	
		100				100				VDI3357-A-193	
		125				135				VDI3357-A-194	
		160				175				VDI3357-A-195	
		200A				175				VDI3357-A-196	
		200B				175				-	
		250A	40			210				-	
		250B	25			225				-	
		300	25			275				-	
		315	40			275				-	

Order Ex. 訂購範例

SZ-DMWP-W-L

Type 品名	Material 材質	Heat Treatment 熱處理	Hardness 硬度	Delivery 交貨日
SZ-DMWP	S45C	Surface Hardened 高頻淬火	HRC 55~	8 Working Days 8 個工作日

Type	W	L	Hole Type	ℓ1	ℓ2	ℓ3	d1	d2	t	VDI Code	
SZ-DMWP	50	80	B	-	25	55	13.5	20	13	VDI3357-A-152	
		100				75				VDI3357-A-153	
		125				100				VDI3357-A-154	
		160				135				VDI3357-A-155	
		200				175				VDI3357-A-156	
		315				275				-	
	80	50	A	30	-	-	9	15	9	VDI3357-A-161	
		80	B	-	25	55	13.5	20	13	VDI3357-A-162	
		100				75				VDI3357-A-163	
		125				100				VDI3357-A-164	
		160				135				VDI3357-A-165	
		200				175				VDI3357-A-166	
		250				210				-	
		315	275	-							
		100	50	A	50	-	-	13.5	20	13	VDI3357-A-171
			80	B	-	25	75	13.5	20	13	VDI3357-A-172
			100				100				VDI3357-A-173
			125				135				VDI3357-A-174
	160		175				VDI3357-A-175				
	200		210				VDI3357-A-176				
	250A		40				210				-
	250B		D	50	25	225	-				
	315	B	-	40	275	-					